

NDAA/TAA
COMPLIANT PRODUCTS

4K
ULTRA HD
30fps

2.8mm
Fixed
Lens



4K Resolution Universal HD / Analog Star-Light Plus™ 2.8mm Fixed Lens WDR **5YEAR** Warranty

Summary

Featuring Star-Light Plus™ color in near-total darkness, the 4K Universal HD over Coax[®] cameras are NDAA/TAA compliant, delivering crystal-clear images and support HD-Analog, HD-TVI, HD-CVI and all legacy analog signal. The weather-resistant bullet cameras are IP66 rated and can be controlled via the same coax cable using UTC. All Star-Light Plus™ 4K cameras are engineered to work with our VMAX[®] A1 4K™ DVRs using your existing coax infrastructure for a cost-effective, high resolution surveillance solution.

Features

- Universal HD over Coax[®] technology with HD-Analog, HD-TVI, HD-CVI and all legacy analog signal support
- Star-Light Plus™ color in near-total darkness technology
- 1/1.8" image sensor
- 4K at 15fps, 4MP or 2.1MP/1080p at real-time 30fps
- 2.8mm fixed lens
- True wide dynamic range (WDR)
- OSD control via coaxial (UTC)
- 100' Smart IR™ with intelligent camera sync.
- Smart DNR™ 3D digital noise reduction
- True day/night mechanical IR cut filter
- De-Fog™ extreme weather image compensation
- Easy icon driven OSD menu with built-in joystick
- Programmable privacy zones
- Auto gain control (AGC)
- Backlight compensation (BLC)
- Auto white balance (AWB)
- NDAA/TAA compliant
- IP66 environmental-rated dust-tight and water-resistant
- 5 year warranty

Accessories (Optional)





DWC-BLJUNC
Junction box



DWC-PMB-BU
Pole mount

Dimensions

Unit: Inch (mm)



UNIVERSAL
HD COAX
UTC

Specifications

IMAGE	
Image sensor	4K 1/1.8" CMOS
Active pixels	3864 (H) x 2176 (V)
Scanning system	Progressive scan
Frequency	60Hz
Signal technology	Universal HD over Coax [®] technology with HD-Analog, HD-TVI, HD-CVI to 4K and CVBS
Synchronization	Internal
Resolution	Max 3840 x 2160
Minimum scene illumination	0.1 lux (color) 0 lux (B/W)
Video output	4K @ 15fps 4MP/1440p @ 30fps 2.1MP/1080p @ 30fps
2nd video output	CVBS output for video testing
LENS	
Focal length	2.8mm
Lens type	Fixed lens
Field of view (FoV)	106.5°
IR distance	100ft range
OPERATIONAL	
Shutter mode	Auto
Shutter speed	1/30-1/30,000
Backlight compensation (BLC)	Yes
Star-Light™ (sense-up)	Off-x32 (not available at 4K)
Wide Dynamic Range (WDR)	Double shutter true WDR
Wide dynamic Range (WDR) dB	120dB
Smart DNR™ 3D digital noise reduction	3D/2D DNR
White balance	Yes
Highlight masking exposure (HME)	Yes
Dynamic range compression (DRC)	Yes
Day/night	Auto, day (color), night (B/W)
Mirror/flip	Yes
Auto gain control	Max 60dB
Motion detection	Yes
Privacy zones	Yes
Sharpness	Yes
Gamma	0.45
De-fog	Yes
RS485/UTP built-in	UTC
ENVIRONMENTAL	
Operating temperature	-4°F - 122°F (-20°C - 50°C)
Operating humidity	10-90% RH (non-condensing)
IP rating	IP66-rated
Other certifications	FCC, CE, ROHS
ELECTRICAL	
Power requirements	DC12V
Power consumption	DC12V (LED off): 3W, 250mA DC12V (LED on): 4.2W, 352mA
MECHANICAL	
Material	Aluminum bullet housing
Dimensions	8.83" x 3.81" (224.5 x 96.7 mm)
Weight	1.65lbs (0.75kg)
Warranty	5 year warranty