

960H Digital Video Recorder **DW-VC 4**



Summary

The VMAX960H CORE™ is an advanced H.264 embedded digital video recorder that records real-time at 960H Resolution. This DVR offers the unparalleled image quality of the VMAX960H, at an affordable cost for small and mid-size applications. In addition, the DVR offers great features such as Free DDNS, One Touch Backup and Playback, True DVR Health Check with E-mail Notifications and is supported by our popular mobile application. The VMAX960H CORE™ is available with up to 4 Terabytes of storage.

Features


- 34% MORE Resolution with True 960x480 Display Recording
- Pivot™ Central Management Software, Up to 128CH
- Mobile Application for iPhone, iPad, iPod, Android Smart Phones and Tablets, and Kindle Fire
- · MAC Compatible Remote ACS Software
- · Intuitive Graphical User Interface (GUI)
- HDD Calculation and Auto Recording Configuration
- Event Notifications via Email. Text and Pivot™ CMS
- Advanced H.264 Embedded DVR
- Multiplex Live, Playback, Recording, Backup, Network, Configuration
- · Record 30 Frames per Second on Every Channel
- 1 Audio Input, 1 Audio Output
- · 4 Sensor Input, 1 Relay Output
- Simple & Free DDNS Service
- Easy Web-Based Client with Multi-User Access
- Scheduled Network Backup
- Watermark Verification (Digital Signature Verification)
- Help Menu on Major Functions
- · Auto & Manual Firmware Upgrade Available
- Import/Export Configuration Between Multiple DVRs
- USB Mouse, IR Remote Control, GUI

Available Models

- DW-VC 161T
- DW-VC 162T
- DW-VC 163T
- DW-VC 164T

Dimensions (unit: mm)





Specifications

| VIDEO | | 4 Observation |
|---|----------------------------|---|
| Video Input | F D. | 4 Channels |
| Video Live | Frame Rate | 1~30fps |
| | Resolution | 960x480, 960x240, 480x240 |
| Video Output | | HD Output, Composite, SPOT |
| Audio | Input | 1 Input (Via Phone Jack) |
| | Output | 1 Output (Via Phone Jack) |
| | Audio Codec | PCM |
| Alarm | Sensor Input | 4 Input |
| | Alarm Out | 1 Output |
| Operating System | | Embedded Linux |
| Serial | | 2xRS485 for PTZ Camera & Controller, 2xUSB 2.0 |
| User Interface | Menu Display | Graphical User Interface (GUI) |
| | Control Methods | IR Remote Control, USB Mouse |
| Screen Display Mode | | 1, 4, Sequence |
| Screen Resolution | | 1920x1080P, 1280x1024, 1024x768 |
| PERFORMANC | Ε | |
| Recording | Compression | H.264 |
| | | Schedule, Event, Time-Lapse, Panic, Continuous, |
| | Recording Mode | Pre & Post Event, Motion, Recording Configuration per Channel |
| | Pre Recording | 1~5 Seconds |
| | Post Recording | 5~15 Seconds |
| | Recording Rate | 120fps @ All Resolution (NTSC/PAL) |
| | Recording Resolutions | Full 960H Real-Time Recording, 30fps @ All Resolutions |
| | Playback Rate | 120fps @ All Resolution (NTSC/PAL) |
| Playback | Playback Resolution | Full 960H Real-Time Playback, 30fps @ All Resolutions |
| | | 7 7 7 |
| | Fast Forward Functions | x1/16, x1/8, x1/4, x1/2, x1, x2, x4, x8, x16, x32 |
| | Playback Functions | First Data, Last Data, Date/Time, Record Table, |
| | | Calendar, Bookmark, System Log |
| Storage | HDD Interface | 1 HDD |
| | Max. Internal HDDs | Up to 4TB (1HDD x 4TB) |
| | External Storage | USB Flash Drive, USB HDD, DVD |
| | HDD Interface Type | SATA-II, SATA-III |
| | HDD Health Check | Temperature, S.M.A.R.T. with E-mail Notifications |
| Features | Camera Color Control | Brightness, Contrast, Saturation, Hue |
| | Digital Zoom | Yes (Live & Playback) |
| | Software Upgrade | USB Flash Drive, Network Upgrade, FTP Remote Upgrade |
| | Mobile Client | Mobile App for Apple & Android Smart Phones & Tablets |
| | Covert Channel | Yes (Live & Playback) |
| NETWORK | | |
| Network Connection | | Ethernet (1 x Megabit 10/100 Mbps) |
| Maximum User Connections | | 10 Simultaneous Connections |
| Streaming Access | Transmission Speed Live | 120/100fps @ 960H and CIF (NTSC/PAL) |
| | Protocols | Static, DDNS, DHCP, uPnP, RTSP |
| | Web Viewer | Live, Playback, & Configuration up to 10 Multiple Connections |
| | Client Monitoring Software | ACS (Client S/W), MAC (Apple S/W), Pivot (CMS S/W) |
| GENERAL | One it wormoring software | Add (dilett of W), WAC (Apple of W), 1 Wot (divid of W) |
| | aturo / Humiditu | 5 ~ 40°C (41 ~ 104°F) |
| Operating Temperature / Humidity Operating Humidity | | |
| operating Humidit | | Less than 80% (Non-Condensing) |
| Electrical | Power Requirement | 12V 3.33A D/C |
| | Power Consumption | 30.96W |
| Dimensions | | 14.2 x 14.3 x 2.6 inch (360.68 x 363.22 x 66.04mm) |
| Weight | | 8.4 lbs (3.8 kg) |

*Specifications subject to change without notice.



866.446.3595 sales@dwcc.tv digital-watchdog.com