

Transporter



E-mail Event Notifications G-sensor Technology


- Automatic Collision Recording
- Unusual Breaking Verification
- Acceleration Detecting

GPS Driven by Google Map


- Vehicle location and Traveled Route Detail
- Time and Date Verification with Free Mapping CMS



Dimensions (Unit : mm)



Rear View



Front View

Summary

The Transporter provides the cutting edge of mobile recording solutions for any type of transportation security application. This mobile DVR was built upon industrial specifications that offer the most reliable mobile solutions. These industrial specifications allow the mobile DVR to withstand any harsh conditions, such as shock, vibration, and temperature. Explore our new Transporter, and enjoy the peace of mind from the most reliable in-vehicle technology.

Features

- Advanced H.264 Linux Embedded DVR
- Live View, Remote Playback, File Backup, E-mail Notification
- 30fps at D1, 120fps at CIF
- 4Ch Video / 4Ch Audio Recording
- 4 Sensor Input, 1 Sensor Output
- G-Sensor Technology: Automatic Collision Recording, Unusual Breaking Verification, Acceleration Detecting
- GPS Antenna Included
- GPS Driven by Google Map: Vehicle Location and Traveled Route Detail; Verifies Time and Date with Free Mapping CMS
- Wireless Communication: Access Any Transporter via External Wireless Bridge or Wireless Mobile Router
- One Touch Video Backup
- One Touch Reverse Playback
- Web-based Client w/ Multi-User Access
- Automatic Private IP Addressing
- Simple & Free DDNS Support
- NTP (Network Time Protocol)
- Watermark Verification
- Network Bandwidth Control
- Configuration Import/Export
- E-mail Event Notifications
- Central Management Software up to 64 Channels
- Support Blackberry, iPhone, and 3G Phone
- USB Mouse, IR Remote Control GUI
- 3 Year Limited Warranty

Available Model Numbers

4 Channel
DW-VMAX-TP500G

Specifications

| MODEL | | Transporter |
|------------------------------------|--------------------|--|
| Compression Algorithm | | Video : H.264, Audio : G723.1 |
| Video | Input | 4 Ch |
| Display Speed | | 120/100 fps |
| Screen Split | | 1, 4, and PIP |
| Video Out | Monitor | 1 Composite |
| | Resolution | 720x480 (NTSC), 720x576 (PAL) |
| Recording Speed | 352x240/288 (CIF) | 120/100 fps |
| | 720x240/288 (2CIF) | 60/50 fps |
| | 720x480/576 (4CIF) | 30/25 fps |
| Recording Resolution | | NTSC : 352x240, 720x240, 720x480 |
| Recording Modes | | Continuous, Scheduled, Sensor-Activated, & Motion Detection Recording Pre- & Post-Alarm Recording |
| Search & Playback | Speed | x1, x2, x4, x8, x16, x32 |
| | Functions | 1Ch, 4Ch (Multi-Channel Playback) Time Bar, Calendar Search, Text-in-Search, Event Search |
| Audio In / Out | | 4 In / 1 Out |
| Alarm In / Out | | 2 In / 2 Out |
| PTZ Control & Port | | Virtual Joy-Stick Control On-Screen by Mouse Pan/Tilt/Zoom/Focus/Iris, RS-485 Port |
| LAN | | 10/100 Base-Tx Ethernet (RJ45) - Fixed IP, DHCP, & DDNS Network Transmission: 120fps @ CIF |
| Network Transmission | Function | Live Monitoring, Remote Playback, and File Backup (Triplex-on-Remote) |
| | | Remote & E-Mail Notification |
| Mobile Device Support | | iPhone, Blackberry (2011), 3G mobile (2011) |
| Remote Management | Software | CMS |
| | Web | Live Monitoring, Playback & System Configuration |
| Backup | External | Local Backup by USB Memory Stick and Network Backup by CMS |
| | | Multi-Language, System Upgrade by USB |
| Advanced Functions | | Configuration Import & Export, Watermark, AVI File Backup Warning Alarm for System Over-Temperature |
| System Operation | | IR Remote Controller, USB Mouse |
| Power | | 12V-36 DC, 64 Watt |
| Storage Temperature and Humidity | | -20~60 °C / 20~95% RH |
| Dimension and Weight | | 218(W)x56(H)x255(D), 1.3kg (2.93 lbs) without HDD |
| Operating Temperature and Humidity | | -20 ~ 50 °C / -4 ~ 122 °F / 20~80% RH |
| Certification | | CE & FCC |

(*) Specification is subject to change without prior notice.